


VOLLPROTEC SWL

Halteclip passend zu Schutzschlauch PA6, PA12

Clip pour la gaine de protection PA6, PA12



Farbe: schwarz (grau 01 durch 06 ersetzen)

Couleur: noir (gris remplacer 01 par 06)

Art.Nr. schwarz No art.noir	Schlauch-Ø Ø-gaine ND mm	A A	B B	C C	H H	M M	Gewicht Poids g	VE UE Stk./pcs
04 0632 0701	7	22	17	20	13	4	3.00	100
04 0632 1001	10	25	22	20	13	5	4.00	100
04 0632 1201	12	27	25	20	15	5	5.00	100
04 0632 1701	17	33	31	20	19	5	6.80	100
04 0632 2301	23	42	40	20	23	6	9.00	50
04 0632 2901	29	47	46	20	26	6	10.20	30
04 0632 3601	36	56	56	20	31	6	13.80	20
04 0632 4801	48	70	70	20	39	6	21.80	10

O-Ringe / Joints ORJ



Dichtungen / Joints PLJ



Temperaturbereich: -30°C...+100°C
NBR 70 elastomer
Plage de température: -30°C...+100°C
NBR 70 élastomer

Temperaturbereich: -40°C...+200°C
verformbar und asbestfrei
Plage de température: -40°C...+200°C
déformable et sans amiante

Art. Nr. No. art.	Schlauch-Ø Ø-gaine ND mm	Øint. mm	Ø mm	Gewicht Poids g	Verpackungseinheit Unité d'emballage Stk./pcs.
ORJ-07	7	6,35	1,3	0,05	100
ORJ-10	10	10,0	1,3	0,06	100
ORJ-12	12	11,5	1,5	0,10	100
ORJ-17	17/18	16,0	1,8	0,18	100
ORJ-23	23	22,0	2,0	0,30	50
ORJ-29	29	29,0	2,0	0,39	30
ORJ-36	36	34,0	2,3	0,56	20
ORJ-48	48	44,6	2,4	0,84	10

Art. Nr. No. art.	Gewinde Filetage mm	Øint. mm	Øext. mm	Gewicht Poids g	Verpackungseinheit Unité d'emballage Stk./pcs.
PLJ-M12	M 12	12,0	18,0	0,32	100
PLJ-M16	M 16	16,0	22,0	0,42	100
PLJ-M20	M 20	20,0	27,0	0,62	100
PLJ-M25	M 25	25,0	35,0	1,25	50
PLJ-M32	M 32	32,0	43,0	1,63	30
PLJ-M40	M 40	40,0	55,0	2,93	20
PLJ-M50	M 50	50,0	69,0	4,75	10
PLJ-M63	M 63	60,0	82,0	3,34	10