




Zwilling's Aderendhülsen / Embouts de fils doubles

Elektrolytkupfer, verzinkt mit Kunststoffkragen aus Polypropylen Cuivre électrolytique, étamé, isolant: polypropylène (105°C)
(105°C)




mm ²	L = mm	Ax B = mm	Standard	Farbcode/Art. Nr. Code couleurs/no. Art.		VE Stk UE pcs
				DIN	Telemecanique	
2,00 x 0,50	8,00	5,00 x 3,00	A 4601 / 8D09	A 4601 / 8D05	A 4601 / 8D05	100
2,00 x 0,50	10,00	5,00 x 3,00	A 4601 / 10D09	A 4601 / 10D05	A 4601 / 10D05	100
2,00 x 0,50	12,00	5,00 x 3,00	A 4601 / 12D09	A 4601 / 12D05	A 4601 / 12D05	100
2,00 x 0,75	8,00	5,50 x 3,00	A 4602 / 8D05	A 4602 / 8D06	A 4602 / 8D02	100
2,00 x 0,75	10,00	5,50 x 3,00	A 4602 / 10D05	A 4602 / 10D06	A 4602 / 10D02	100
2,00 x 0,75	12,00	5,50 x 3,00	A 4602 / 12D05	A 4602 / 12D06		100
2,00 x 0,75	18,00	5,50 x 3,00	A 4602 / 18D05	A 4602 / 18D06	A 4602 / 18D02	100
2,00 x 1,00	8,00	5,80 x 3,20	A 4603 / 8D11	A 4603 / 8D04	A 4603 / 8D04	100
2,00 x 1,00	12,00	5,80 x 3,20	A 4603 / 12D11	A 4603 / 12D04	A 4603 / 12D04	100
2,00 x 1,00	18,00	5,80 x 3,20	A 4603 / 18D11	A 4603 / 18D04	A 4603 / 18D04	100
2,00 x 1,50	8,00	6,50 x 3,60	A 4604 / 8D04	A 4604 / 8D01	A 4604 / 8D01	100
2,00 x 1,50	12,00	6,50 x 3,60	A 4604 / 12D04	A 4604 / 12D01	A 4604 / 12D01	100
2,00 x 1,50	18,00	6,50 x 3,60	A 4604 / 18D04	A 4604 / 18D01	A 4604 / 18D01	100
2,00 x 2,50	10,00	8,00 x 4,50	A 4605 / 10D14	A 4605 / 10D14	A 4605 / 10D06	100
2,00 x 2,50	12,00	8,00 x 4,50	A 4605 / 12D14	A 4605 / 12D14	A 4605 / 12D06	100
2,00 x 2,50	18,00	8,00 x 4,50	A 4605 / 18D14	A 4605 / 18D14	A 4605 / 18D06	100
2,00 x 4,00	12,00	9,00 x 5,20	A 4606 / 12D06	A 4606 / 12D06	A 4606 / 12D09	100
2,00 x 4,00	18,00	9,00 x 5,20	A 4606 / 18D06	A 4606 / 18D06	A 4606 / 18D09	100
2,00 x 6,00	12,00	11,40 x 6,20	A 4607 / 12D11	A 4607 / 12D11	A 4607 / 12D12	100
2,00 x 6,00	18,00	11,40 x 6,20	A 4607 / 18D11	A 4607 / 18D11	A 4607 / 18D12	100
2,00 x 10,00	12,00	13,40 x 7,60	A 4608 / 12D13	A 4608 / 12D04	A 4608 / 12D03	100
2,00 x 10,00	18,00	13,40 x 7,60	A 4608 / 18D13	A 4608 / 18D04	A 4608 / 18D03	100
2,00 x 16,00	16,00	17,20 x 9,50	A 4609 / 16D12	A 4609 / 16D14	A 4609 / 16D05	50
2,00 x 16,00	25,00	17,20 x 9,60	A 4609 / 25D12	A 4609 / 25D14	A 4609 / 25D05	50



Aderendhülsen AWG / Embouts de fils AWG

Elektrolytkupfer, verzinkt mit vergrössertem Kunststoffkragen aus Polypropylen (105°C) Cuivre électrolytique, étamé, isolant à collet plus grand: polypropylène (105°C)



AWG	mm ²	L = mm	D = mm	Standard	Farbcode/Art. Nr. Code couleurs/no. Art.		VE Stk UE pcs
					DIN	Telemecanique	
20	0,50	8,00	2,90	A 4620 + 809	A 4620 + 805	A 4620 + 805	500
18	0,75	8,00	3,40	A 4619 + 805	A 4619 + 806		500
18	1,00	8,00	3,50	A 4618 + 811	A 4618 + 804	A 4618 + 804	500
16	1,50	8,00	4,00	A 4616 + 804	A 4616 + 801	A 4616 + 801	500
14	2,50	8,00	4,20	A 4605 / 814	A 4605 / 814	A 4605 / 806	100
12	4,00	10,00	4,80	A 4606 / 1006	A 4606 / 1006	A 4606 / 1009	100
10	6,00	12,00	6,30	A 4607 / 1201	A 4607 / 1211	A 4607 / 1212	100

363902 / 363903